

Sponsor: Lihao Chen Yamashin-Filter Corp. Uragocho 5-chome 2931-22 Yokosuka, Kanagawa, 237-0062 JAPAN

Bacterial Filtration Efficiency (BFE) Final Report

Test Article: 200721-6

200721-11

Purchase Order: RD66-355 Study Number: 1340608-S01

Study Number: 1340608-501 Study Received Date: 11 Sep 2020

Testing Facility: Nelson Laboratories, LLC 6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0004 Rev 18

Deviation(s): None

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts downstream. A suspension of *Staphylococcus aureus* was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at $1.7 - 3.0 \times 10^3$ colony forming units (CFU) with a mean particle size (MPS) of $3.0 \pm 0.3 \ \mu m$. The aerosols were drawn through a six-stage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side: Either
BFE Test Area: ~40 cm²

BFE Flow Rate: 28.3 Liters per minute (L/min)

Conditioning Parameters: 85 ± 5% relative humidity (RH) and 21 ± 5°C for a minimum of 4 hours

Test Article Dimensions: ~160 mm x ~164 mm

Positive Control Average: 2.5 x 10³ CFU Negative Monitor Count: <1 CFU

MPS: 3.1 µm





Sean Shepherd electronically approved for

James Luskin

13 Oct 2020 17:28 (+00:00)
Study Completion Date and Time

Study Director

801-290-7500

jb



Results:

Test Article	Percent BFE (%)
200721-6	>99.9
200721-11	>99.9 ^a

^a There were no detected colonies on any of the Andersen sampler plates for this test article.

The filtration efficiency percentages were calculated using the following equation:

$$\% BFE = \frac{C - T}{C} \times 100$$

C = Positive control average

T = Plate count total recovered downstream of the test article Note: The plate count total is available upon request

sjb